



PS-3205UWg

Three Port Wireless Print Server (IEEE 802.11g) **2 USB 1.1 Printer Ports + 1 Parallel Printer Port**

Easy Installation and Configuration (Web Based)

The print server's easy-to-use windows installation wizard allow for quick installation and setup. The print server can also be conveniently configured from any network client that support web-browsing.

Supports Peer-to-Peer and Server-Based Printing

Supports both Peer-to-Peer and Server-based printing. LAN clients can connect directly with the print server to execute printing jobs (Peer-to-Peer printing); or clients can send print jobs first to a server (queuing jobs) and allow the server to connect with the print server to execute the printing jobs (Server-based printing).

Provides Complete Printing Methods

The print server provides LPR and Raw Printing methods. You can choose the best printing method according to your environment.

Supports Major Operating Systems

The print server is compatible with all major operating systems used today, for example Windows 95 / 98 / Me / NT / 2000 / XP, NetWare (3.x above), MAC OS and Unix/Linux environments.


Supports DHCP Server/Client

The printer server can act as a DHCP server, allowing your LAN clients to automatically obtain an IP address or it can act as a DHCP client allowing for easy integration to your existing network.

Fault-Tolerant Firmware Upgrades

Users need not worry about errors occurring in the midst of an upgrade, thus preventing the print server from operating. The print server's fault-tolerant upgrade function allows for re-upgrades should problems occur during the initial upgrade.





Features

- Provides one 10/100Mbps auto-sensing port that complies with IEEE 802.3 and 802.3u standards
- Provides three printer ports that can connect to printer's USB/parallel port
- Supports IEEE 802.11g/b Wireless LAN (AdHoc mode/Infrastructure mode) with up to 54Mbps data transfer rate
- Supports 64/128 Bit key length WEP encryption
- Supports TCP/IP, IPX/SPX, AppleTalk network protocols
- Supports LPR, IPP, Raw Printing
- Supports Peer-to-Peer Printing (TCP/IP)
- Supports Server-based printing (Novell NetWare and Windows)
- Compatible with all major operating systems (Windows 95/98/Me/NT/2000/XP, NetWare (3.x above), MAC OS and Unix/Linux)
- Supports DHCP (both client and server) protocol
- Efficient print job transfer using DMA (Direct Memory Access).
- Supports bi-directional capability, able to get information from printers
- Supports Web-based management, Windows Configuration Utility
- Provides easy-to-use installation, setup and diagnostic programs.
- Supports Fault-Tolerant Upgrade capability

Specification

Product	PS-3205UWg
CPU	ADMtek ADM5120 (MIPS R4000 175MHz)
Super I/O	Attansic AT761F
RF Module	Inprocomm 802.11g mini-PCI Card
Flash	2 MB NOR Flash
RAM	16 MB SDRAM
Printer Ports	USB 1.1 x 2 + DB-25 x 1
LAN Port	10/100M UTP Port x 1
Power	12V DC, 1A Power Adaptor
Dimension	30(H)* 187(W)* 100(D) mm
Temperature	10~40 °C
Humidity	10~90% (Non-Condensing)
Certification	FCC Class B, CE Mark, C-Tick

Edimax Worldwide

Taiwan/Headquarters

Edimax Technology Co., Ltd.

TEL : 886-2-22995648

FAX : 886-2-22995647

E-mail : service@edimax.com.tw

China

Beijing Edimax Science

& Technology Co., Ltd.

TEL : 8610-82665568

FAX : 8610-82665325

E-mail : support@edimax.com.cn

USA

Edimax Computer Company

TEL : 1-408-496-1105

FAX : 1-408-980-1530

E-mail : support@edimax.com

Latin America

Edimax Latin America

TEL : 1-786-845 8099

FAX : 1-786-331 8490

E-mail : sales_latinamerica@edimax.com

Europe

Edimax Technology Europe B.V.

TEL : 31-499-377344

FAX : 31-499-372647

E-mail : support-europe@edimax.com.tw

U.K.

Edimax Technology (UK) Ltd.

TEL : +44-(0)-1908-255881

FAX : +44-(0)-1908-255700

E-mail : support-uk@edimax.com.tw

